



SolarEdge Power Optimizer

Module Add-On For North America

P300 / P400 / P405



POWER OPTIMIZER

PV power optimization at the module-level

- Up to 25% more energy
- Superior efficiency (99.5%)
- Mitigates all types of module mismatch losses, from manufacturing tolerance to partial shading
- Flexible system design for maximum space utilization
- Fast installation with a single bolt
- Next generation maintenance with module-level monitoring
- Module-level voltage shutdown for installer and firefighter safety



SolarEdge Power Optimizer

Module Add-On for North America

P300 / P400 / P405

	P300 (for 60-cell modules)	P400 (for 72 & 96-cell modules)	P405 (for thin film modules)	
INPUT				
Rated Input DC Power ⁽¹⁾	300	400	405	W
Absolute Maximum Input Voltage (Voc at lowest temperature)	48	80	125	Vdc
MPPT Operating Range	8 - 48	8 - 80	12.5 - 105	Vdc
Maximum Short Circuit Current (Isc)		10		Adc
Maximum DC Input Current		12.5		Adc
Maximum Efficiency		99.5		%
Weighted Efficiency		98.8		%
Overvoltage Category		II		
OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING SOLAREEDGE INVERTER)				
Maximum Output Current		15		Adc
Maximum Output Voltage	60		85	Vdc
OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM SOLAREEDGE INVERTER OR SOLAREEDGE INVERTER OFF)				
Safety Output Voltage per Power Optimizer		1		Vdc
STANDARD COMPLIANCE				
EMC	FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3			
Safety	IEC62109-1 (class II safety), UL1741			
RoHS	Yes			
INSTALLATION SPECIFICATIONS				
Maximum Allowed System Voltage	1000			Vdc
Dimensions (W x L x H)	Pxxx-2 series	141 x 212 x 40.5 / 5.55 x 8.34 x 1.59		mm / in
	Pxxx-5 series	128 x 152 x 27.5 / 5 x 5.97 x 1.08	128 x 152 x 35 / 5 x 5.97 x 1.37	128 x 152 x 48 / 5 x 5.97 x 1.89
Weight (including cables)	Pxxx-2 series	950 / 2.1		gr / lb
	Pxxx-5 series	770 / 1.7	930 / 2.05	930 / 2.05
Input Connector	MC4 Compatible			
Output Wire Type / Connector	Double Insulated; MC4 Compatible			
Output Wire Length	0.95 / 3.0	1.2 / 3.9		m / ft
Operating Temperature Range	-40 - +85 / -40 - +185			°C / °F
Protection Rating	Pxxx-2 series	IP65 / NEMA4		
	Pxxx-5 series	IP68 / NEMA6P		
Relative Humidity	0 - 100			%

⁽¹⁾ Rated STC power of the module. Module of up to +5% power tolerance allowed.

PV SYSTEM DESIGN USING A SOLAREEDGE INVERTER ⁽²⁾	SINGLE PHASE	THREE PHASE 208V	THREE PHASE 480V	
Minimum String Length (Power Optimizers)	8	10	18	
Maximum String Length (Power Optimizers)	25	25	50	
Maximum Power per String	5250	6000	12750	W
Parallel Strings of Different Lengths or Orientations		Yes		

⁽²⁾ It is not allowed to mix P405 with P300/P400/P600/P700 in one string.

